



Profile system
□ Glass folding door with thermally insulated aluminum profiles □ Bottom-loaded construction □ The construction depth of the profiles is 75 mm □ Rear-ventilated wooden cladding inside □ Option of flush or weathered bottom track □ The flush bottom track is particularly suitable for use in "Barrier-free dwellings" according to DIN 18 025 □ Panel open to the inside or outside □ Opening of panels by sliding to one side or to both sides □ Flush running and guide tracks □ Height variations and expansions may be compensated
Tests □ U _W up to 1,5 W/m ² k (with glazing U _g = 0,7 W/m ² k) □ Air permeability class 4 according to EN 12207 □ Rain tightness class E900 according to EN 12208 □ Resistance to wind load class B4 according to EN 12210 □ Airborne sound insulation value R _W = 36 dB according to DIN EN ISO 140-3 □ Burglar-resistance up to resistance class 2 (WK2)
Fittings All fittings are concealed within the profiles Low-maintenance, non-corroding and failsafe hardware components Locking of panels in top and bottom track and/or via mushroom head-lock engaging into the frame or adjacent panel Locking and unlocking of panels via flat handles with locking device for burglar resistance Optionally fitted with different lock types Hinges are secured against knocking-out of the pivot pins (burglar resistance) An open turn panel may be securely fixed to the adjacent panel by panel catchers
Running assembly Easy adjustment due to a height-adjustable carriage system The running assemblies are located above the water drainage area Low-noise, wear-, heat- and cold-resistant rollers
Sealing and ventilation ☐ Using EPDM gaskets at two levels guarantees rain— and wind–proofness
Glazing □ Glazing configuration between 28 mm is possible □ Subsequent replacement of panes without difficulty



Testreport No.23-21/09E, No. 40-29/09 und No. 40-30/09



Testreport ATT 11.11.801.01



tested SUNFLEX Quality



Testreport 1286-001-10

Corner angles 90°-180° with or without corner post (only available with special corner post/special design!)


Тур I




Тур А



Тур I




Тур А




Corner angles 90°-180° (only available with special corner post/special design!)

Тур I



Тур А



Other floor plan geometries upon request





Safety

The panels are locked and unlocked by means of a user-friendly single-handed manipulation of robust flat handles. For additional safety, different types of locks are available.




Mushroom head lock

For optimal tightness and burglar resistance the doorway panel (turn panel) is laterally being connected to the frame or the adjacent panel through a mushroom head lock.



Safety function panel catcher

In any opening position of the folding system an open turn panel may be safely locked to the adjacent panel by means of safety function panel catchers and be carried along in a controlled




Burglar resistance

All external hinges are additionally secured by means of a safety screw against knocking out of the hinge bolts.




Proper handle series

Handles matching the profile design guarantee a harmonized overall picture of the folding system in closed state and a small panel package in open state.




Twin-Lock locking mechanism

To guarantee additional safety, the optionally available twin-lock locking mechanism offers a maximum of security.



Height compensation


The height of the installed folding system may be easily adjusted by a few hand grips, only - this is important in case of eventual structure sagging.




Assembly

The assembly shoes allow a fast and trouble-free assembly of the frame and a fine adjustment of the vertical frame profiles in the closing range.


Tel: 01522 869 679
Email: info@parkfarmdesign.co.uk
www.parkfarmdesign.co.uk



Details at even panel partition in one direction



Details at even and uneven panel partition in two directions




Ref.	Section	Description	Page
	SF55c-000	Vertical-Section, timber clad designs (classic, modern (soft), squared)	6
F	SF55c-001	Vertical-Section, connection bottom track / inside folding	6
F	SF55c-003	Vertical-Section, connection bottom track / outside folding	6
F	SF55c-005	Vertical-Section, connection flush bottom track	6
Α	SF55c-002 Vertical-Section, connection top track / inside folding		7
Α	SF55c-004	Vertical-Section, connection top track / outside folding	7
F	F SF55c-007 Vertical-Section, strengthening profile for balustrade / inside folding		7
Α	A SF55c-008 Vertical-Section, strengthening profile for overhead light / inside folding		7
Α	SF55c-009	Vertical-Section, connection top track overhead light I inside folding	8
E	SF55c-101	5c-101 Horizontal-Section, blind frame – panel closing section / inside folding	
E	SF55c-102	Horizontal-Section, blind frame - panel closing section / outside folding	8
C	SF55c-103	Horizontal-Section, panel - panel / hinge outside	8
D	SF55c-104	Horizontal-Section, panel - panel / hinge inside	9
В	SF55c-105	Horizontal-Section, vertical post - panel / hinge inside	9
В	SF55c-106	Horizontal-Section, vertical post - panel / hinge outside	9
D	SF55c-107	Horizontal-Section, midrail	9
G	SF55c-108	Horizontal-Section, panel – panel closing section	10
E	SF55c-109	Horizontal-Section, frame extension 35 mm	10
E	SF55c-110	Horizontal-Section, frame extension 70 mm	10
E	SF55c-111	SF55c-111 Horizontal-Section, 90°- connection profile	
E	SF55c-112 Horizontal-Section, 135°- connection profile		11





Ref.	Section	Description	Page
D	SF55c-113	Horizontal-Section, sliding post / hinge outside	11
D	SF55c-121	Horizontal-Section, sliding post / hinge inside	11
D	SF55c-114	Horizontal-Section, sliding post incl. strengthening / hinge outside	11
D	SF55c-115	Horizontal-Section, closing section - sliding post (e.g. 1L/2R) / outside folding	12
D	SF55c-116	Horizontal-Section, closing section - sliding post (e.g. 1L/2R) / inside folding	12
Е	SF55c-117	Horizontal-Section, blind frame - panel closing section incl. sliding post (e.g. 2R) / outside folding	12
E	SF55c-118	Horizontal-Section, blind frame - panel closing section incl. sliding post (e.g. 2R) / inside folding	12
	SF55c-119	Horizontal-Section, profil section – sliding post(e.g. 2L/2R) / outside folding	13
	SF55c-120	Horizontal-Section, profil section – sliding post(e.g. 2L/2R) / inside folding	13






Vertical-Section,

strengthening profile for balustrade / inside folding





Vertical-Section,

strengthening profile for over-head light / inside folding

System:

SF55c


Detail-No.: SF55c-008

System:

SF55c


Detail-No.: SF55c-007








ail: info@parkfarmdesign.co.uk





















Tel: 01522 869 679 Email: info@parkfarmdesign.co.uk

